



Asian Electron Co., Ltd.

6F-1, No.150, Jian Yi Road, Zhonghe Dist., New Taipei City 235, TAIWAN, R.O.C.

TEL: 886-2-8226-5158

FAX:886-2-82265150

<http://www.asian-electron.com>

e-mail: sales@asian-electron.com



PST1000W Series Pure Sine Wave Inverter

Features

- Pure Sine Wave output (THD < 3%) R Load
- Output frequency: 50/60Hz switch
- Bypass Function
- Wired remote control
- Loading and Temperature controlled cooling fan
- Advanced microprocessor
- Protection: Input Undervoltage
Input Overvoltage
Overload
Short circuit
Low battery alarm
Over temperature

Electrical Performance : 1000W

Specification	Model					
Item	YK-PST12100	YK-PST24100	YK-PST48100	YK-PST12100E	YK-PST24100E	YK-PST48100E
Continuous Output	1000W					
Maximum Output Power	1150W (3Min.)					
Surge Rating	2000W					
Input Voltage	12V	24V	48V	12V	24V	48V
Input Voltage Range	10-16VDC	20-32VDC	42-62VDC	10-16VDC	20-32VDC	42-62VDC
DC Input Over Voltage Alarm	15.5VDC	31.0VDC	61.0VDC	15.5VDC	31.0VDC	61.0VDC
DC Input Over Voltage Shut-down	16.0VDC	32.0VDC	62.0VDC	16.0VDC	32.0VDC	62.0VDC
DC Input Under Voltage Alarm	10.5VDC	21.0VDC	43.0VDC	10.5VDC	21.0VDC	43.0VDC
DC Input Under Voltage Shut-down	10.0VDC	20.0VDC	42.0VDC	10.0VDC	20.0VDC	42.0VDC
Output Voltage	100/110/115/120V(Switch Selectable) RMS±3%			200/220/230/240V(Switch Selectable) RMS±3%		
Frequency	50/60Hz ± 0.05% (Switch Selectable)					
Peak Output Current	18A			9A		
Efficiency (full load)	86%	88%	89%	87%	90%	92%
No Load Current Draw	1.11A	0.52A	0.32A	1.17A	0.59A	0.40A
Output Waveform	R Load Pure Sine Wave < 3% THD					
P.F.	1.0			1.0		
Protection	Overload, Short Circuit, Reverse Polarity (Fuse), Over/Under Input Voltage, Over Temperature.					
Digital Display	OVP, UVP, OTP, OLP, VAC, AMP, WATT, VDC, TEMP, Hz					
Safety	EN60950-1:2006 & IEC60950-1: 2005(2nd Edition)					
EMC	FCC Class B			EN55022:1998/ A1:2000/A2:2003 (Class B) EN55024: 1998/ A1:2001/A2:2003 EN61000-3-2: 2000/ A2:2005 EN61000-3-3: 1995/A1:2001 IEC61000-4-2:1995/ A1:1998/A2:2000 IEC61000-4-3:2002/A1:2002 IEC61000-4-4:2004 IEC61000-4-5:1995/ A1:2000 IEC61000-4-6:1996/A1:2001 IEC61000-4-8:1993/A1:2000 IEC61000-4-11:2004		
Remote Control Unit	Optional					
AC Input	110VAC			220VAC		
AC Frequency	(50Hz ~ 60 Hz) ± 3%			(50Hz ~ 60 Hz) ± 3%		
AC Frequency	4~6ms			4~6ms		
Operating Temperature	-20°C to 50°C					
Storage Temperature	-30°C to 70°C					
Cooling	Loading and Temperature controlled cooling fan					
Dimensions	310 (L) × 179 (W) × 81 (H) mm					
Weight	3.8 kgs					

The specifications are subject to change without notice.