



Asian Electron Co., Ltd.

6F-1, No.150, Jian Yi Road, Chung Ho City, Taipei Hsien, Taiwan

TEL.: +886 2-8226-5158, FAX: +886 2-8226-5150

[Http://www.asian-electron.com](http://www.asian-electron.com)

E-mail: asian.yk@msa.hinet.net



Battery Charger

Specification:

Spec.	Model No.	YK-C1212	YK-C2512	YK-C1424	YK-C0824	YK-C0848
		YK-C1212E	YK-C2512E	YK-C1424E	YK-C0824E	YK-C0848E
		12V/12A	12V/25A	24V/14A	24V/8A	48V/8A
Input supply voltage		110V±10% 220V±10%	110V±10% 220V±10%	110V±10% 220V±10%	110V±10% 220V±10%	110V±10% 220V±10%
Charging end voltage (V1)		14.4V	14.4V	28.8V	28.8V	54.4V
Maintenance charger (V2)		13.41V	13.41V	27.2V	27.2V	51.2V
Max. charging current		12A	25A	14A	8A	8A
Operating temperature range		0°C~50°C	0°C~50°C	0°C~50°C	0°C~50°C	0°C~50°C
Main frequency		50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz
Net weight		2.1kgs	2.7kgs	2.7kgs	2.1kgs	2.7kgs
Dimension (mm)		230x205x82	290x205x82	290x205x82	230x205x82	290x205x82

