



# Asian Electron Co., Ltd.

## 1U1KVA 19" Rack Mount Pure Sine Wave Inverters

### Features:

1. Digital display
2. Bypass function (STS)
3. Advanced microprocessor
4. Loading controlled cooling fan
5. Output frequency: 50 / 60Hz switch
6. RS – 232 interface / remote controls port / Wire connection to PC
7. Protection : Input undervoltage      Overload      Short circuit  
Low battery alarm      Input overvoltage      Over temperature



Specification	Model								
Item	YK-PSW121KVA (1U)	YK-PSW241KVA (1U)	YK-PSW481KVA (1U)	YK-PSW121KVAE (1U)	YK-PSW241KVAE (1U)	YK-PSW481KVAE (1U)			
Continuous Output Power	850W (1KVA)								
Surge Rating	900W/1Mins , 950W/3Sec , 1000W/1Sec								
Input Voltage	12V	24V	48V	12V	24V	48V			
Output Frequency	50/60Hz ± 0.05% ( Switch Selectable)								
Peak Output Current	15A			9A					
Efficiency (full load)	86%	88%	89%	87%	90%	92%			
No Load Current Draw	0.75A	0.4A	0.3A	0.7A	0.35A	0.25A			
Output Waveform	R Load Pure Sine Wave <3% THD								
Output Voltage Regulation	100/110/115/120V (Switch Selectable) RMS±3%			200/220/230/240V (Switch Selectable) RMS±3%					
P.F.	0.85			0.85					
Input Voltage Range	10-16VDC	20-32VDC	42-62VDC	10-16VDC	20-32VDC	42-62VDC			
Protection	Overload, Short Circuit, Reverse Polarity (Fuse), Input Undervoltage, Input Overvoltage, Over Temp.								
Digital Display	OVP, UVP, OTP, OLP, VAC, AMP, WATT, VDC, TEMP, Hz								
Safety	UL60950-1			EN60950-1					
EMC	FCC Class B			EN 55022:1998/ A1: 2000/A2:2003( <b>Class B</b> ) EN 55024: 1998/ A1:2001/A2:2003 EN 61000-3-2: 2000/A2: 2005 EN 61000-3-3: 1995/A1: 2001 IEC 61000-4-2:1995/ A1:1998/A2:2000 IEC 61000-4-3:2002/A1: 2002 IEC 61000-4-4: 2004 IEC 61000-4-5:1995/A1: 2000 IEC 61000-4-6:1996/A1: 2001 IEC 61000-4-8: 1993/A1:2000 IEC 61000-4-11: 2004					
Interface Control Port	RS-232 With Baud Rate 2400,4800, 9600, 19200 (Switch Selectable)								
AC Input	110V			220V					
AC Input Frequency	(50Hz ~ 60 Hz) ± 3%			(50Hz ~ 60 Hz) ± 3%					
Bypass	4~6ms			4~6ms					
Operating Temperature Range	-20°C to 60°C								
Storage Temperature Range	-30°C to 70°C								
Dimensions	416.8(L) × 424.0(W) × 44.0(H) mm								
Weight	7.5kgs								

Remark: The specifications are subject to change without notice.